


Kolíky izolované

Použitý materiál: kolík - měď galvanicky cínovaná
 Teplotní stálost: Polyvinilchlorid (PVC) -10°C až +75°C
 Polycarbonat (PC) -150°C až +115°C, krátkodobě +130°C
 10-95mm² Polyamid (Nylon, PA) -55°C až +125°C

Průřez (mm ²)	Označení		Rozměry (mm)				Hmotnost (kg/100ks)	Balení (ks)
	PVC	PC, PA	l ₁	l ₂	d	b		
0,1-0,5	-	KI 0,5-8/PA	8,0	6,5	3,0	1,5	0,020	100
0,5-1,5	KI 1,5-8	KI 1,5-8/PC	8,0	17,8	3,9	1,8	0,055	100
	KI 1,5-10	KI 1,5-10/PC	10,0	19,8	3,9	1,8	0,060	100
	KI 1,5-12	KI 1,5-12/PC	12,0	22,0	3,9	1,8	0,065	100
1,5-2,5	KI 2,5-8	KI 2,5-8/PC	8,0	18,3	4,9	1,8	0,055	100
	KI 2,5-10	-	10,0	19,8	4,9	1,8	0,060	100
	KI 2,5-12	KI 2,5-12/PC	12,0	22,0	4,9	1,8	0,065	100
	KI 2,5-17	KI 2,5-17/PC	17,0	27,0	4,9	1,8	0,100	100
4-6	KI 6-10	-	10,0	24,4	6,7	2,2	0,170	100
	KI 6-12	-	12,0	26,6	6,7	2,2	0,175	100
	KI 6-14	KI 6-14/PC	14,0	28,6	6,7	2,2	0,180	100
10	-	KI 10-12	14,5	35,1	8,0	4,2	0,310	100
16	-	KI 16-14	18,0	41,1	9,2	5,5	0,440	100
25	-	KI 25-16	20,3	45,0	11,1	6,8	0,730	100
35	-	KI 35-20	24,5	55,0	13,6	8,0	1,340	50
50	-	KI 50-26	26,0	59,0	15,5	9,5	2,100	50
70	-	KI 70-31	31,0	69,0	18,0	11,0	3,200	50
95	-	KI 95-31	31,0	71,0	20,7	12,5	4,700	50




Kolíky izolované ploché

Použitý materiál: kolík - měď galvanicky cínovaná
 izolace- Polyvinilchlorid (PVC) -10°C až +75°C

Průřez (mm ²)	Označení	Rozměry (mm)				Hmotnost (kg/100ks)	Balení (ks)
		l ₁	l ₂	d	b		
0,5-1,5	KIPL 1,5-12	10,0	20,0	4,3	2,3	0,055	100
	KIPL 1,5-18	18,0	28,0	4,3	2,5	0,060	100
1,5-2,5	KIPL 2,5-12	10,0	20,0	4,8	2,5	0,055	100
	KIPL 2,5-18	18,0	28,0	4,8	2,5	0,060	100
4-6	KIPL 6-12	10,0	23,5	6,5	3,0	0,146	100
	KIPL 6-16	16,0	29,5	6,5	4,8	0,155	100


Kolíky izolované ploché, zahnuté



Použitý materiál: měď
 Povrchová úprava: galvanické cínování
 izolace: Polyvinilchlorid (PVC) -10°C až +75°C

Průřez (mm ²)	Označení	Rozměry (mm)					Hmotnost (kg/100ks)	Balení (ks)
		l ₁	l ₂	d	b	a		
0,5-1,5	KIPPL 1,5/30	10,0	26,5	4,3	3,0	2,1	0,085	100
	KIPPL 1,5/46	10,0	26,5	4,3	4,6	2,1	0,095	100
1,5-2,5	KIPPL 2,5/30	10,0	26,5	4,8	3,0	2,1	0,100	100
	KIPPL 2,5/46	10,0	26,5	4,8	4,6	2,1	0,115	100
4-6	KIPPL 6/30	13,5	30,0	6,5	3,0	2,4	0,160	100
	KIPPL 6/46	13,5	30,0	6,5	4,6	2,4	0,175	100

Kolíky neizolované



Použitý materiál: měď
 Povrchová úprava: galvanické cínování
 Vyrobeno dle normy: DIN 46230

Průřez (mm ²)	Označení	Rozměry (mm)				Hmotnost (kg/100ks)	Balení (ks)
		l ₁	l ₂	d	b		
0,1-0,5	KN 0,5-10	10,0	14,0	1,0	1,4	0,050	100
0,5-1,5	KN 1,5-8	8,0	15,0	1,6	1,9	0,051	100
	KN 1,5-10	10,0	17,0	1,6	1,9	0,056	100
	KN 1,5-12	12,0	19,0	1,6	1,9	0,060	100
1,5-2,5	KN 2,5-8	8,0	15,0	2,3	1,9	0,063	100
	KN 2,5-10	10,0	17,0	2,3	1,9	0,067	100
	KN 2,5-12	12,0	19,0	2,3	1,9	0,072	100
4-6	KN 6-10	10,0	16,0	3,6	2,7	0,150	100
	KN 6-12	12,0	18,0	3,6	2,7	0,155	100
	KN 6-14	14,0	20,0	3,6	2,7	0,160	100
10	KN 10	14,5	23,5	4,8	4,3	0,270	100
16	KN 16	18,0	28,0	5,9	5,5	0,390	100
25	KN 25	20,3	32,0	7,0	7,0	0,630	100
35	KN 35	24,5	39,0	8,9	8,0	1,170	100
50	KN 50	26,0	45,0	10,0	9,5	1,790	50
70	KN 70	31,0	55,0	11,5	11,0	2,920	50
95	KN 95	31,0	55,0	13,5	12,5	4,300	50